

 Safety Data Sheet

 According to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

 Effective Date: 17 May 2022
 Revision 10
 DCR # 3289

SECTION 1: Identification	
1.1. Identification	
Product form :	Resin suspension in storage buffer
Trade name :	Actigel T
Product code :	2703
1.2. Relevant identified uses of the substat	nce or mixture and uses advised against
	Storage buffer for chromatography media.
1.3. Details of the supplier of the safety da	ta sheet
Sterogene Bioseparations, Inc. 1949 Kellogg Avenue, Carlsbad, CA 92008 Telephone Number: (760) 929-0455 Contact Person: James Danford jdanford@sterogene.com	
1.4. Emergency telephone number	
Emergency number :	(951) 447-9994
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mix	ture
GHS-US classification	
Flam. Liq. 3 H226 - Flammable liquid and vapor Eye Irrit. 2A H319 - Causes serious eye irritation STOT SE 1 H370 - Causes damage to organs Full text of H-statements: see section 16	
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US) :	GHS02 GHS07 GHS08
Signal word (GHS-US) :	Danger
Hazard statements (GHS-US) :	H226 - Flammable liquid and vapor H319 - Causes serious eye irritation H370 - Causes damage to organs
Precautionary statements (GHS-US) :	 P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P260 - Do not breathe vapors, spray, mist P264 - Wash hands thoroughly after handling P270 - Do not eat, drink or smoke when using this product P280 - Wear eye protection, protective gloves P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor P337+P313 - If eye irritation persists: get medical advice/attention P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder to extinguish P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

Actigel T Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

2.3. Other hazards

Other hazards which do not result in classification

: This material contains methanol, which, when ingested, has caused acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

The only hazards identified with this material are those associated with the storage buffer.

Name	Product identifier	%	GHS-US classification
Ethanol	(CAS No) 64-17-5	19	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Asp. Tox. 1, H304
methanol	(CAS No) 67-56-1	1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of H-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.	
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/injuries after inhalation	: May cause headache and dizziness.
Symptoms/injuries after skin contact	: May cause skin irritation / dermatitis. May cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Eye irritation.
Symptoms/injuries after ingestion	: This material contains methanol, which, when ingested, has caused acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Water spray. Dry powder. Alcohol resistant foam. Carbon dioxide.		
Unsuitable extinguishing media	: Do not use water jet.		
5.2. Special hazards arising from the sub-	stance or mixture		
Fire hazard	: Flammable liquid and vapor. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.		
Explosion hazard	: No direct explosion hazard.		
Reactivity	: Flammable liquid and vapor. Stable under normal conditions of use.		
5.3. Advice for firefighters			
Firefighting instructions	: Exercise caution when fighting any chemical fire. Use fire-extinguishing media appropriate for surrounding materials.		
Protective equipment for firefighters	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.		
SECTION 6: Accidental release measures			

6.1.	Personal precautions, protective equipment and emergency procedures	
6.1.1.	For non-emergency personnel	
Emerge	ncy procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, spray, and mist. Avoid contact with skin and eyes.

DCR # 3289

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

cording to the federal final rule of hazard communication	on revised on 2012 (HazCom 2012)	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for containme	ent and cleaning up	
For containment	: Stop leak, if possible without risk.	
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.	
Other information	: Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		
For further information refer to section 8: Exposu	ure-controls/personal protection.	
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe vapors, spray, and mist. Avoid contact with skin and eyes.	
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, includi	ng any incompatibilities	

Storage conditions Incompatible materials Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.Strong acids. Strong oxidizers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)			
ACGIH	ACGIH STEL (ppm)	1000 ppm	
ACGIH	Remark (ACGIH)	URT irr	
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
methanol (67-56-1)			
ACGIH	ACGIH TWA (ppm)	200 ppm	
ACGIH	ACGIH STEL (ppm)	250 ppm	
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea	
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³	
OSHA	OSHA PEL (TWA) (ppm)	200 ppm	

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Impermeable protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.

: In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls

Respiratory protection

: Avoid release to the environment.

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and	d chemical properties		
Physical state	: Aqueous solution		
Color	: Colorless		
Odor	: Alcohol Odor		
Odor threshold	: No data available		
pH	: No data available		
Melting point	: Not applicable		
Freezing point	: No data available		
Boiling point	: No data available		
Flash point	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosive limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: No data available		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Solubility	: No data available		
Log Pow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
0.0 Others in forms of loss			

9.2. Other information

No additional information available

SECT	ION 10: Stability and reactivity		
10.1.	Reactivity		
Flamma	able liquid and vapor. Stable under normal conditions of use.		
10.2.	Chemical stability		
Stable u	under normal conditions.		
10.3.	Possibility of hazardous reactions		
No dangerous reactions known under normal conditions of use. No polymerization.			
10.4.	Conditions to avoid		
Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition.			
10.5.	Incompatible materials		
Strong acids. Strong oxidizers.			
10.6.	Hazardous decomposition products		
Under normal conditions of storage and use, hazardous decomposition products should not be produced. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.			

SECTION 11: Toxicological information 11.1. Information on toxicological effects		
ikely routes of exposure	: Oral; Inhalation; Skin and eye contact	
Acute toxicity	: Not classified	
Ethanol (64-17-5)		
LD50 oral rat	7060 mg/kg	
LC50 inhalation rat (mg/l)	124.7 mg/l/4h	
Effective Date: 17 May 2022 Rev. 10	DCR # 3289	4/7

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

methanol (67-56-1)	
LD50 oral rat	6200 mg/kg
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Causes damage to organs.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause headache and dizziness.
Symptoms/injuries after skin contact	: May cause skin irritation / dermatitis. May cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Eye irritation.
Symptoms/injuries after ingestion	: This material contains methanol, which, when ingested, has caused acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.

: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
5012 mg/l 48 hours - Daphnia
9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
275 mg/l
4432 mg/l
9.6 mg/l Daphnia magna
28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and degradability 12.2.

No additional information available

12.3. Mobility in soil

No additional information available

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Waste treatment methods	: Dispose of in conformance with all applicable federal, state and local laws and regulations.		
Additional information	: Flammable vapors may accumulate in the container.		

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 14: Transport information

Department of Transportation (DOT)

Not regulated by DOT

: 49CFR 173.150(e)(1,2) states that aqueous solutions of alcohol containing 24 percent or less alcohol by volume and no other hazardous material can be re-classified as a combustible liquid and are not subject to the requirements.

Air transport

Not regulated by IATA - Not regulated for transport by air.

: IATA Special Provision A58 states that aqueous solutions containing 24 percent or less alcohol by volume are not subject to the regulations.

SECTION 15: Regulatory information

15.1. US Federal regulations		
Ethanol (64-17-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Methanol (67-56-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
SARA Section 313 - Emission Reporting	1.0 %	

15.2. International regulations

Ethanol (64-17-5)	
Listed on the Canadian DSL (Domestic Substan	ces List)
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
methanol (67-56-1)	
Listed on the Canadian DSL (Domestic Substan	ces List)
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

15.3. US State regulations

Ethanol (64-17-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
methanol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 16: Other information	
Sources of Key data	: Data arise from reference works and literature.
Revision date	: 15 Dec 2020
Abbreviations and acronyms	: ACGIH - American Conference of Government Industrial Hygienists
	Eye dam – Eye damage
	PEL- Permissible Exposure Level
	STEL- Short-Term Exposure Limit
	TWA- Time Weighted Average
	URT irr -upper respiratory tract irritation

Full text of H-statements:

Acute toxicity (dermal) Category 3
Acute toxicity (inhalation) Category 3
Acute toxicity (oral), Category 3
Aspiration hazard, Category 1
Serious eye damage/eye irritation, Category 2A
Flammable liquids Category 2
Flammable liquids, Category 3
Specific target organ toxicity (single exposure) Category 1
Highly flammable liquid and vapor
Flammable liquid and vapor
Toxic if swallowed
May be fatal if swallowed and enters airways
Toxic in contact with skin
Causes serious eye irritation
Toxic if inhaled
Causes damage to organs

The information contained herein is presented in good faith and is believed to be correct as of the date prepared, but does not purport to be all inclusive. Regulatory requirements are subject to change and may differ depending on location. It is the customer's responsibility to ensure that its activities are in compliance with local, state, federal or provincial laws.

No information contained in this document is to be taken as a warranty for which Sterogene Bioseparations, Inc. bears responsibility. Sterogene shall not be held liable for any damage resulting from handling or from contact with the product. All materials may present hazards and should be used with caution. Although specific hazards are described, we cannot guarantee that these are the only hazards that exist.